



Reorder No: 0408



# Tech Specs:

| Color            | Greer    |
|------------------|----------|
| Fragrance        | Faint    |
| Form             | Liquid   |
| Phosphates       | None     |
| FlashPoint       | 212F     |
| pH               | 9-10     |
| Specific Gravity | 1.07     |
| Viscosity        | Thir     |
| Foam             | Moderate |
| Biodegradable    | 100%     |
| Shelf Life       | 1 Yea    |

| Available Packages |                        |
|--------------------|------------------------|
| 0408-275           | 275 Gallon Tote        |
| 0408-55            | 55 Gallon Plastic Drum |
| 0408-30            | 30 Gallon Plastic Drum |
| 0408-15            | 15 Gallon Plastic Drum |
| 0408-5.25          | 2x2.5 Gallon Jugs      |
| 0408-5             | 5 Gallon Plastic Pail  |
| 0408-4             | 4 Gallon Case          |

# SubZero

# Low Temp Floor & Freezer Cleaner

Use: Floor & Surface Cleaning - Freezers

# What is Sub Zero?

Sub Zero is specially designed for applications where cold temperature is commonly a problem. This product will remove dirt, grime, fat and grease deposits from floors, freezer lockers, walls, equipment, storage racks. While being tough on soils and grease, it will not freeze down to  $-40^{\circ}F$ .

Freezers are important to many facilities such as food processing plants, and to shut them down costs time and money. Sub Zero will allow you to continue operations while keeping your facility clean and sanitary.

# **Benefits:**

- Removes heavy natural fats and oils.
- USDA approved.
- Will not freeze down to -40°F.
- Removes heavy grease and oils from deep cracks and imperfections in almost any floor.
- Can be used as a heavy duty cleaner, degreaser, or floor scrub.

# **Directions For Use:**

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area. For professional use only by trained personnel.

#### FLOOR SCRUB MACHINES:

Equip machine with aggressive brushes such as steel wire and fill reservoir with cleaner. Double-scrub procedure will give best results. Lay down solution with scrubbing action and allow solution to remain on surface 5 minutes - then lower squeegee blade, scrubbing again and pick up.

# CONVENTIONAL ROTARY FLOOR MACHINE:

Equip machine with aggressive brush such as steel wire. Spray, mop or spread cleaner on surface. Scrub area and allow to remain 5 minutes. Scrub again and pick up soiled solution with wet-vacuum or mop.

# MANUAL CLEANING:

Apply cleaner by spray mop or sponge and follow by aggressive double brushing or scrubbing. Pick up soiled solution with wet-vacuum, mop or wiping