



Reorder No: 0424



# Tech Specs:

Color	Clear
Fragrance	.Characteristic
Form	Liquid
Phosphates	None
FlashPoint	212F
рН	13.5
Specific Gravity	<i>.</i> 1.02
Viscosity	Thin
Foam	Moderate
Biodegradable	100%
Shelf Life	1 Year

Available Packages	
0424-275	275 Gallon Tote
0424-55	55 Gallon Plastic Drum
0424-30	30 Gallon Plastic Drum
0424-15	15 Gallon Plastic Drum
0424-5.25	2x2.5 Gallon Jugs
0424-5	5 Gallon Plastic Pail
0424-4	4 Gallon Case

# Super Strip Premium Low Odor Floor Stripper

Use: Floor Stripper

## What is Super Strip?

A professional strength, fast acting no-rinse stripper that quickly emulsifies floor waxes, sealers and finishes. Super Strip will strip floors in less time and effort than conventional strippers due to its extremely aggressive nature, allowing cost savings by decreasing labor time. Will liquefy multiple layers of acrylic finishes at one time, making cleanup easy with an autoscrubber or floor machine. Lower odor allows for use in more places than traditional strippers.

### Benefits:

- Strips quickly and easily.
- Doesn't leave behind a slimy mess.
- Low foam allows for effortless automated cleanup.
- Lower odor formulation.
- Removes multiple layers in one shot.
- Rinse Free.
- No neutralization required.

#### **Directions For Use**

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area.

Wet floors may be slippery so prevent pedestrian traffic with signs or barricades.

Dilute with from 1 to 5 parts water when manually stripping. Automatic scrubber solutions should be 1 part concentrate with 10 parts water.

Liberally apply to small area of approximately 100 square feet covering completely and to the baseboards.

Allow 3 to 5 minutes for chemical action, but do not allow to dry on the floor. Agitate with mop or machine scrub, then pick up solution using a wet vac or automatic scrubber.

Damp mop with clean water to remove residue.

Make sure to use proper protective clothing when applying this or any chemical Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area.

www.syntecpro.com