

:W₋₄

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/09/2017 Revision date: 12/15/2017 Supersedes: 03/16/2017

Version: 2.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : CW-4
Product code : 1016

1.2. Recommended use and restrictions on use

Recommended use : Heavy-duty detergent

1.3. Supplier

Synthetic Labs 24 Victory Lane

Dracut, MA 01826 - United States T 800.255.4050 - F 978.957.5122

www.syntecpro.com

1.4. Emergency telephone number

Emergency number : Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1A Serious eye damage/eye irritation Category 1 Causes severe skin burns and eye damage

Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : Causes severe skin burns and eye damage

Causes serious eye damage

Precautionary statements (GHS US) : Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands, forearms and face thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Specific treatment (see supplemental first aid instruction on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

07/14/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Sodium hydroxide	(CAS-No.) 1310-73-2	20 – 30	Acute Tox. 1 (Oral), H300 Skin Corr. 1, H314 Eye Dam. 1, H318
Tetrasodium ethylenediaminetetraacetate	(CAS-No.) 64-02-8	1 – 5	Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : T

fire

: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

07/14/2020 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CW-4	
No additional information available	
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
No additional information available	
Sodium hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH Ceiling (mg/m³)	2 mg/m³
Remark (ACGIH)	URT, eye, & skin irr
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL (TWA) (mg/m³)	2 mg/m³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Liquid.Color: redOdor: odorless

07/14/2020 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold : No data available

рН : 14 pH solution 13.5 - 14Melting point : Not applicable : No data available Freezing point **Boiling point** No data available Flash point No data available Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C No data available Relative density : No data available : 1.04 g/m³ Specific gravity / density : Soluble in water. : No data available No data available

Solubility : Soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)

Skin corrosion/irritation : Causes severe skin burns.

pH: 14

Serious eye damage/irritation : Causes serious eye damage.

pH: 14

07/14/2020 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated

exposure

: Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
LC50 fish 1	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 Daphnia 1	625 mg/l (24 h, Daphnia magna, Literature study)
Sodium hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)

12.2. Persistence and degradability

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance
Sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Partition coefficient n-octanol/water (Log Pow)	-2.6
Bioaccumulative potential	Not bioaccumulative.
Sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Sodium hydroxide (1310-73-2)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

07/14/2020 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide), 8, II

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Sodium Hydroxide

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25

passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living guarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1760 CORROSIVE LIQUID, N.O.S., 8, II

07/14/2020 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : 1760

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S. Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

Transport document description (IATA) : UN 1760 Corrosive liquid, n.o.s., 8, II

UN-No. (IATA) : 1760

Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

Class (IATA) : 8 - Corrosives

Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 1000 lb

15.2. International regulations

CANADA

Tetrasodium ethylenediaminetetraacetate (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Component	State or local regulations
Sodium hydroxide(1310-73-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/15/2017

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

07/14/2020 EN (English US) 7/7