

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 03/09/2017 Revision date: 01/18/2018 Supersedes: 03/20/2017 Version: 2.1

: Mixture
: Classic TLC
: 1396
on use
: Detergent, Carpet cleaning (liquids)
: Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053
ixture
Causes severe skin burns and eye damage Causes serious eye damage
autionary statements
: Danger
Causes severe skin burns and eye damage Causes serious eye damage
 Do not breathe mist, spray, vapors. Wash hands, forearms and face thoroughly after handling. Wear eye protection, protective gloves. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Disodium Metasilicate	(CAS-No.) 6834-92-0	1 – 5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335
Tetrasodium ethylenediaminetetraacetate	(CAS-No.) 64-02-8	1 – 5	Eye Dam. 1, H318
Ethylene Glycol Monobutyl Ether	(CAS-No.) 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Alcohols, Ehoxylated	(CAS-No.) 68439-46-3	1 – 5	Acute Tox. 4 (Oral), H302

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and effect	s (acute and delayed)
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.
4.3. Immediate medical attention and spe	cial treatment, if necessary
Treat symptomatically.	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishi	-
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Specific hazards arising from the che	
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Special protective equipment and protecti	ecautions for fire-fighters
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release meas	ures
6.1. Personal precautions, protective equ	ipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Monday, March 26, 2012 / Rules and Regulations
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for con	tainment and cleaning up
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13	
SECTION 7: Handling and store	age
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, i	ncluding any incompatibilities
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
SECTION 8: Exposure controls	/personal protection
8.1. Control parameters	
Classic TLC	
No additional information available	

No additional information available		
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
No additional information available		
Disodium Metasilicate (6834-92-0)		
No additional information available		
Alcohols, Ehoxylated (68439-46-3)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (ppm)	1 ppm	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) (ppm)	1 ppm	
OSHA PEL (STEL) (ppm)	5 ppm	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA) (ppm)	5 ppm	
NIOSH REL (ceiling) (mg/m ³)	9 mg/m³	
Ethylene Glycol Monobutyl Ether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (ppm)	20 ppm	

8.2.	Appropriate engineering controls		
	riate engineering controls nmental exposure controls	Ensure good ventilation of the work station.Avoid release to the environment.	
8.3.	Individual protection measures/Perso	nal protective equipment	

3. Individual protection measures/Personal protective equipment
Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical p	roperties
9.1. Information on basic physical and ch	emical properties
Physical state	: Liquid
Appearance	: Liquid.
Color	: clear
Odor	: Fresh
Odor threshold	: No data available
pH	: 12.5
pH solution	: 11.5 – 12
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.03 g/m³
Molecular mass	: 1.03 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
9.2. Other information	

No additional information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
The product is non-reactive under normal conditions of use, storage and transport.		
10.2. Chemical stability		
Stable under normal conditions.		
10.3. Possibility of hazardous reactions		
No dangerous reactions known under normal conditions of use.		
10.4. Conditions to avoid		
None under recommended storage and handling conditions (see section 7).		
10.5. Incompatible materials		
No additional information available		

07/14/2020

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological informatio	n		
11.1. Information on toxicological effects			
Acute toxicity (oral)	: Not classified		
	: Not classified		
Acute toxicity (dermal)			
Acute toxicity (inhalation)	: Not classified		
Tetrasodium ethylenediaminetetraacetate (64	Tetrasodium ethylenediaminetetraacetate (64-02-8)		
LD50 oral rat	> 2000 mg/kg (Rat, Oral)		
Disodium Metasilicate (6834-92-0)			
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral)		
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))		
LC50 inhalation rat (mg/l)	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))		
Alcohols, Ehoxylated (68439-46-3)			
LD50 oral rat	1378 mg/kg (Rat, Oral)		
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)		
Ethylene Glycol Monobutyl Ether (111-76-2)			
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)		
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))		
LC50 inhalation rat (ppm)	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))		
Skin corrosion/irritation	: Causes severe skin burns.		
	pH: 12.5		
Serious eye damage/irritation	: Causes serious eye damage.		
	pH: 12.5		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		
Specific target organ toxicity – single exposure	: Not classified		
Disodium Metasilicate (6834-92-0)			
Specific target organ toxicity – single exposure	May cause respiratory irritation.		
Specific target organ toxicity – repeated exposure	: Not classified		
Agnization boyond			
Aspiration hazard	: Not classified		
Viscosity, kinematic	: No data available		
Symptoms/effects after skin contact	: Burns.		
Symptoms/effects after eye contact	: Serious damage to eyes.		
Symptoms/effects after ingestion	: Burns.		
SECTION 12: Ecological information			
12.1. Toxicity			
	· Before neutralisation, the product may represent a danger to aquatic organisms		

: Before neutralisation, the product may represent a danger to aquatic organisms.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)		
LC50 fish 1	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)	
EC50 Daphnia 1	625 mg/l (24 h, Daphnia magna, Literature study)	
Disodium Metasilicate (6834-92-0)		
LC50 fish 1	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)	
EC50 Daphnia 1	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
Ethylene Glycol Monobutyl Ether (111-76-2)		
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)	
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)	

12.2. Persistence and degradability

Tetrasodium ethylenediaminetetraacetate (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance	
Chemical oxygen demand (COD)	0.54 - 0.58 g O ₂ /g substance	
Disodium Metasilicate (6834-92-0)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
Alcohols, Ehoxylated (68439-46-3)		
Persistence and degradability	Readily biodegradable in water.	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

Tetrasodium ethylenediaminetetraacetate (64-02-8)		
Partition coefficient n-octanol/water (Log Pow)	-2.6	
Bioaccumulative potential	Not bioaccumulative.	
Disodium Metasilicate (6834-92-0)		
Bioaccumulative potential	Bioaccumulation: not applicable.	
Alcohols, Ehoxylated (68439-46-3)		
Bioaccumulative potential	No bioaccumulation data available.	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

Disodium Metasilicate (6834-92-0)		
Ecology - soil	No (test)data on mobility of the substance available.	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Surface tension	65.03 mN/m (20 °C, 2 g/l)	
Ecology - soil	Low potential for adsorption in soil.	

12.5. Other adverse effects

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

15.1. US Federal regulations		
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Disodium Metasilicate (6834-92-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Alcohols, Ehoxylated (68439-46-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	
Ethylene Glycol Monobutyl Ether (111-76-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
15.2. International regulations		
CANADA		
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
Listed on the Canadian DSL (Domestic Substances List)		
Disodium Metasilicate (6834-92-0)		
Listed on the Canadian DSL (Domestic Substances List)		
Alcohols, Ehoxylated (68439-46-3)		
Listed on the Canadian DSL (Domestic Substances List)		
Ethylene Glycol Monobutyl Ether (111-76-2)		
Listed on the Canadian DSL (Domestic Substances List)		
EU-Regulations No additional information available		
National regulations		
No additional information available		

15.3. US State regulations

Component	State or local regulations
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday	r, March 26, 2012 / Rules and Regulations
Revision date	: 01/18/2018
Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 0 Minimal Hazard - Materials that will not burn
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.