

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/09/2017 Revision date: 03/14/2017 Supersedes: 03/14/2017 Version: 2.1

# **SECTION 1: Identification**

### Identification

Product form : Mixture Trade name : No Rinse Product code 6595

#### Recommended use and restrictions on use

: Floor strip products Recommended use

#### 1.3. **Supplier**

Synthetic Labs 24 Victory Lane

Dracut, MA 01826 - United States T 800.255.4050 - F 978.957.5122

www.syntecpro.com

#### **Emergency telephone number**

: Infotrac 24 Hour Medical Emergency Number: 1-800-535-5053 Emergency number

# SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation Category 1A

Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 Causes serious eye damage

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Causes severe skin burns and eye damage Hazard statements (GHS US)

Causes serious eye damage

Precautionary statements (GHS US) Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands, forearms and face thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Specific treatment (see supplemental first aid instruction on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

# Other hazards which do not result in classification

No additional information available

# Unknown acute toxicity (GHS US)

Not applicable

07/14/2020 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene Glycol Monobutyl Ether	(CAS-No.) 111-76-2	15 – 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Monoethanolamine	(CAS-No.) 141-43-5	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Corr. 1, H314 Eye Dam. 1, H318
Sodium hydroxide	(CAS-No.) 1310-73-2	1 – 5	Acute Tox. 1 (Oral), H300 Skin Corr. 1, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

# **SECTION 4: First-aid measures**

# 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

# 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

# 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

#### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

# 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray.

# 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

07/14/2020 EN (English US) 2/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No Rinse								
No additional information available								
Sodium hydroxide (1310-73-2)								
USA - ACGIH - Occupational Exposure Limits								
Local name	Sodium hydroxide							
ACGIH Ceiling (mg/m³)	2 mg/m³							
Remark (ACGIH)	URT, eye, & skin irr							
USA - OSHA - Occupational Exposure Limits								
Local name	Sodium hydroxide							
OSHA PEL (TWA) (mg/m³)	2 mg/m³							
Ethylene Glycol Monobutyl Ether (111-76-2)								
USA - ACGIH - Occupational Exposure Limits								
ACGIH TWA (ppm)	20 ppm							
Monoethanolamine (141-43-5)								
USA - ACGIH - Occupational Exposure Limits								
Local name	Ethanolamine							
ACGIH TWA (ppm)	3 ppm							
ACGIH STEL (ppm)	6 ppm							
Remark (ACGIH)	Eye & skin irr							
USA - OSHA - Occupational Exposure Limits								
Local name	Ethanolamine							
OSHA PEL (TWA) (mg/m³)	6 mg/m³							
OSHA PEL (TWA) (ppm) 3 ppm								

# 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

# 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

07/14/2020 EN (English US) 3/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety glasses

# Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colorless
Odor : characteristic
Odor threshold : No data available

pH : 14

Melting point : Not applicable

Freezing point : 32 °F

Boiling point : No data available No data available Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density No data available Specific gravity / density : 0.98 g/m<sup>3</sup> Solubility : Soluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available

Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available

# 9.2. Other information

Oxidizing properties

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

07/14/2020 EN (English US) 4/9

No data available

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethylene Glycol Monobutyl Ether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (ppm)	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))

Monoethanolamine (141-43-5)	
LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male / female, Experimental value, Dermal)

Skin corrosion/irritation : Causes severe skin burns.

pH: 14

Serious eye damage/irritation : Causes serious eye damage.

pH: 14

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Sodium hydroxide (1310-73-2)								
LC50 fish 1	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)							
EC50 Daphnia 1	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)							

07/14/2020 EN (English US) 5/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene Glycol Monobutyl Ether (111-76-2)						
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)					
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)					
Monoethanolamine (141-43-5)						
LC50 fish 1	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)					
EC50 Daphnia 1	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)					

# 12.2. Persistence and degradability

Sodium hydroxide (1310-73-2)						
Persistence and degradability	Biodegradability: not applicable.					
Chemical oxygen demand (COD)	Not applicable (inorganic)					
ThOD	Not applicable (inorganic)					
Ethylene Glycol Monobutyl Ether (111-76-2)						
Persistence and degradability	Readily biodegradable in water.					
Monoethanolamine (141-43-5)						
Monoethanolamine (141-43-5)  Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.					
. ,	Biodegradable in the soil. Readily biodegradable in water.  0.8 g O <sub>2</sub> /g substance					
Persistence and degradability	, ,					
Persistence and degradability Biochemical oxygen demand (BOD)	0.8 g O <sub>2</sub> /g substance					

# 12.3. Bioaccumulative potential

Sodium hydroxide (1310-73-2)									
Bioaccumulative potential	Not bioaccumulative.								
Ethylene Glycol Monobutyl Ether (111-76-2)									
Partition coefficient n-octanol/water (Log Pow) 0.81 (Test data, 20 °C)									
Bioaccumulative potential	mulative potential Low potential for bioaccumulation (Log Kow < 4).								
Monoethanolamine (141-43-5)									
BCF other aquatic organisms 1	2.3 – 9.2 (BCFWIN, Calculated value)								
Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)								
Bioaccumulative potential Not bioaccumulative.									

# 12.4. Mobility in soil

Sodium hydroxide (1310-73-2)									
Ecology - soil	No (test)data on mobility of the substance available.								
Ethylene Glycol Monobutyl Ether (111-76-2)									
Surface tension	65.03 mN/m (20 °C, 2 g/l)								
Ecology - soil	Low potential for adsorption in soil.								
Monoethanolamine (141-43-5)									
Surface tension	No data available in the literature								
Partition coefficient n-octanol/water (Log Koc) 1.16 (log Koc, Calculated value)									
Ecology - soil	logy - soil Highly mobile in soil.								

# 12.5. Other adverse effects

No additional information available

K	8	Е	C.	П	П	C	ı	J	1	k	3:	П	Ŧ	c	r	1	5	c	a	П	c	4	h	n	G	Ŧ	d	Δ	r	a	П	7	'n	n	9
	_	_	v	ш	ш	ч	ш	ч				_	ш	2	В	м	"	ਹ	а	ш	Ľ	А.	91	ч	C	ш	Ų.	U	ш	а	ч		4	ш	9

13.1.	Disposal methods		
Waste	treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
07/14/2	2020	FN (Fnglish US)	6/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Sodium Hydroxide), 8, II

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Sodium Hydroxide

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number : 15

Other information : No supplementary information available.

#### **Transportation of Dangerous Goods**

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 1760 CORROSIVE LIQUID, N.O.S., 8, II

UN-No. (IMDG) : 1760

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S. Class (IMDG) : 8 - Corrosive substances

07/14/2020 EN (English US) 7/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : II - substances presenting medium danger

Air transport

Transport document description (IATA) : UN 1760 Corrosive liquid, n.o.s., 8, II

UN-No. (IATA) : 1760

Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

Class (IATA) : 8 - Corrosives

Packing group (IATA) : II - Medium Danger

# **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

### Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 1000 lb

# Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Monoethanolamine (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

#### **CANADA**

#### Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

# Ethylene Glycol Monobutyl Ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Monoethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List)

**EU-Regulations** 

No additional information available

**National regulations** 

No additional information available

### 15.3. US State regulations

Component	State or local regulations
Monoethanolamine(141-43-5)	U.S New Jersey - Right to Know Hazardous Substance List
Ethylene Glycol Monobutyl Ether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Sodium hydroxide(1310-73-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/14/2017

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

07/14/2020 EN (English US) 8/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

07/14/2020 EN (English US) 9/9